


NICE Serisi



3174



3176



3177



3178



3186



QUALITY

Product Definition	ISO 2424	Multitroll
Gauge		1/10"
No. of Tufts	ISO 1763	
Pile Fibre	ISO 2424	100% Polypropylene
Pile Weight	ISO 8543	690 gr/m ² ± 5%
Pile Height	ISO 1765	3 mm ± 5%
Primary Backing	ISO 2424	PA/PES non-woven
Tile Backing		Polyflex with non-woven fabric
Total Thickness	ISO 1765	5 mm ± 5%
Total Weight	ISO 8543	4200 gr/m ² ± 7,5%
Tile Size	EN 986	50 x 50 cm (± 19.7" x 19.7") 20
Tiles per box		Contract Class 32
Use Classification	EN 1307	Pass
Abrasion		Pass
Vettermann Test	ISO 10361	Pass
Dimensional Stability	ISO 10361	Pass
Thermal Isolation		

ELEKTROSTATIC PROPERTIES

Static Loading	ISO 2424	Anti-static
Flame Properties		
Reaction to Fire	ISO 1763	
Hot Metal Nut Test	EN130501-1	CFI-SI Low Radius

COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	>5.0
Rubbing, Dry	ISO 105 X12	>4.0
Rubbing, Wet		
Shampoo		
Water	ISO 105 E01	>4.0

GENERAL

Recommended Maintenance	
Pile Direction	
Laying Instructions	

Test results are obtained when cleaned with a dry shampoo method. Directional arrows are printed on the back of each tile. Test results are obtained when laid on wooden floor. Tiles require no underlay, making gluing or nailing and taping the most common on flat dry floor slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 50 m² it is advisable to use double sided adhesive tape on every 50 cm or so.

